

Product Specification

Jet Clear



Description

Translucent Ink Jet film

A matt transparent polyester film with ink and toner receptive top coating.

Adhesive

PERMANENT

Clear aqueous acrylic emulsion adhesive.

Minimum application temperature: +10°C

Temperature range: -20°C to +80°C

The adhesive features good tack and adhesion performance on a wide range of substrates.

Approved for indirect food contact and direct contact on dry and moist non-fatty foods.

Backing

White one side coated bleached kraft paper.

Printing Information

Litho: see Translucent Matt Polyester

Laser: Designed for office use 'desk top' printers - not high speed presses. For high speed see Translucent matt Polyester

Copier: as Laser

Ink Jet: Primarily for office use (address labels etc) - heavy ink coverage should be avoided as drying may be retarded.

Indigo: see PCL3 Digital range Translucent Matt (IDP) Polyester

General:

Availability

Available in ranges:

Digital Office
UltraJet

Disclaimer:

Technical information, statements and recommendations are given in good faith and are based on tests we believe to be reliable, but do not constitute a guarantee or warranty. We give no guarantee as to the suitability of the product for a specific application, this should be tested by the user. Unless otherwise agreed in writing, we only accept liability within the scope of our General Terms and Conditions of Delivery and Payment.

This information sheet replaces all earlier ones. All information subject to change without notice.

© Label Connections Limited 2010. All rights reserved.

www.pclabels.com

File date: Aug 2010

