

Product Specification

Paper Grades



Adhesive

Deep Freeze

Aqueous acrylic emulsion adhesive.

Minimum application temperature: 0°C

Temperature range: -50°C to +60°C

Designed for adhesion to goods to be deep frozen. Labelling of already frozen goods should be handled with care and the surface should be free of ice and moisture.

The acrylic adhesive is designed for safe use in hot fusing toner laser and copier printing.

It is possible to use the adhesive as a 'semi-permanent' for some applications at room temperature.

Regulations

Contact with food

Approved for indirect food contact and direct contact on dry and moist non-fatty foods.
(FDA 21 CFR 175.105 (adhesives))

Toy Safety

The adhesive conforms to the EN71-3 (Toy Safety) Regulations and Packaging (Essential Requirements) Regulations.

Heavy Metals

No heavy metals are used in the manufacturing process and typical contents are less than 1ppm.

The use of self adhesive labels on leather, suede, silk, satin (and other such fabrics) furniture e.g. polished wood and any surface containing natural oils should be avoided. The end user must satisfy themselves that the product is suitable for the required use - please request samples

Warranty:

Information and recommendations are based on our most up to date knowledge and experience. As the products are used outside our control we cannot take any responsibility for any damage which may be caused when using the product.

The product information should be used as a guide only - please request samples for testing if unsure of any aspect of the application or print process compatibility.

This information sheet replaces all earlier ones. All information subject to change without notice.

© Label Connections Limited 2008. All rights reserved.

File date: January 2008

