

Product Specification

Paper Grades



Adhesive

Permanent and Extra Permanent

Aqueous acrylic emulsion adhesive.

Minimum application temperature: 0°C

Temperature range: -20°C to +80°C

Chill grade - ideal for sandwich/chilled food labelling.

Designed for laminates in a wide range of applications. Very good heat resistance which enables trouble free performance in different hot fusing print processes. Good adhesion to cardboard and low energy (e.g. plastic bags) surfaces. Good 'all round' permanent adhesive.

Use Extra Permanent adhesive where higher initial tack is required particularly on tightly curved surfaces and packaging containing a high degree of recycled printers waste pulp.

Regulations

Contact with food

Approved for indirect food contact and direct contact on dry and moist non-fatty foods.
(FDA 21 CFR 175.105 (adhesives))

Toy Safety

The adhesive conforms to the EN71-3 (Toy Safety) Regulations and Packaging (Essential Requirements) Regulations.

Heavy Metals

No heavy metals are used in the manufacturing process and typical contents are less than 1ppm.

The use of self adhesive labels on leather, suede, silk, satin (and other such fabrics) furniture e.g. polished wood and any surface containing natural oils should be avoided. The end user must satisfy themselves that the product is suitable for the required use - please request samples

Warranty:

Information and recommendations are based on our most up to date knowledge and experience. As the products are used outside our control we cannot take any responsibility for any damage which may be caused when using the product.

The product information should be used as a guide only - please request samples for testing if unsure of any aspect of the application or print process compatibility.

This information sheet replaces all earlier ones. All information subject to change without notice.

© Label Connections Limited 2007. All rights reserved.

File date: February 2007

